



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Patent Application of:)
LETOR ET AL.)
)
Serial No. 10/627,414)
)
Filing Date: JULY 25, 2003)
)
For: METHOD AND RELATIVE CIRCUIT)
FOR DETECTING A TORQUE)
VARIATION OF AN ELECTRIC DC)
MOTOR)

TRANSMITTAL OF CERTIFIED PRIORITY DOCUMENT

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:


Transmitted herewith is a certified copy of the
priority European Application No. 02425488.0.

Respectfully submitted,

PAUL J. DITMYER
Reg. No. 40,455
Allen, Dyer, Doppelt, Milbrath
& Gilchrist, P.A.
255 S. Orange Avenue, Suite 1401
Post Office Box 3791
Orlando, Florida 32802
Telephone: 407/841-2330
Fax: 407/841-2343
Attorney for Applicant

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being
deposited with the United States Postal Service as first class
mail in an envelope addressed to: COMMISSIONER FOR PATENTS,
P.O. BOX 1450, ALEXANDRIA, VA 22313-1450, on this 10th day of
February, 2004.





**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

02425488.0

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk



Anmeldung Nr:
Application no.: 02425488.0
Demande no:

Anmeldetag:
Date of filing: 26.07.02
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

STMicroelectronics S.r.l.
Via C. Olivetti, 2
20041 Agrate Brianza (Milano)
ITALIE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Method and relative circuit for detecting a torque variation of an electric DC motor


In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

H02P/

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR



FIELD OF THE INVENTION

The present invention relates in general to devices in which motion is produced by a motor and in particular to the detection of a torque variation of a reversible DC motor, that is the direction of rotation of which may be reversed.

5 BACKGROUND OF THE INVENTION

Sample applications of the present invention is for the detection of an accidental block of an electric motor dedicated to lift and lower a glass window of a car, a garage door and the like. In many applications of reversible electric motors for moving parts that may accidentally be blocked by a number of unpredictable
 10 causes, it may be necessary to detect the presence of an obstacle that stops the motion in order to protect either the motor and/or the transmission organs from overloads that may damage them, or to prevent injuries when the obstacle is a part of the human body (for example a finger, a neck etc.).

Figure 1 schematically depicts a motorized car window system. The glass pane 2
 15 of a door 1 of a car is moved by a DC motor 3 (M). The mechanical transmission 4 between the motor and the glass is sketched with a dashed line.

The motor 3 is driven by a full-bridge stage 5, composed of four switches SW1, SW2, SW3 and SW4 that may be driven in pairs depending on the desired direction of rotation of the motor, and thus of the desired direction (up or down)
 20 of motion of the glass pane 2. The switches SW1 ... SW4 are connected in series along the two parallel branches of the bridge, between the supply nodes 6 and 7. The switches SW1, SW3 are connected in series to form a first branch between the nodes 6 and 7, and the switches SW2 and SW4 are connected in series to form a second branch between the nodes 6 and 7. The motor 3 is connected to the
 25 intermediate nodes 8 and 9 of the two branches of the bridge. Depending from the configuration of the four switches, the current I_M forced through the motor will circulate either in a direction or in the opposite direction determining the direction of rotation of the motor.

The switches SW1 ... SW4 are driven by a control circuit 10 CTRL in function of a start command (H/L) bearing the information of the desired direction of rotation. The control circuit 10 produces the four control phases for the respective switches SW1 ... SW4. The bridge 5 and the circuit 10 are generally powered by a regulator
5 11 (REG) of the car battery (not depicted) voltage (V_{bat}) providing a regulated DC voltage V_{cc} . If required, the supply voltages of the bridge 5 and of the control circuit 10 may even be different.

Generally, the current I_M flowing in the motor 3 is monitored and the instantaneous current information is input to the control circuit 10. In Figure 1, the
10 sensing of the current I_M is indicated by an ampere meter symbol 12 in series with the motor 3. In practice, this sensing may be done on a sense resistor connected in series to one or to both branches of the bridge 5.

The instantaneous current information is used by the control circuit 10 in order to protect the motor against accidental overloads that may damage it. The current
15 sensing may be substituted or associated to the sensing of the temperature of the motor in order to switch off electric supply when the temperature exceeds a certain limit.

In any case, current and/or temperature sensing involve the fixing of thresholds and are generally unsuitable for sensing torque variations of the motor.

20 For instance, application of the type of a motorized window or door with automatic detection of the end of the run it may often be required also a so-called "anti pinch" function to prevent crushing with excessive force an accidental obstacle such to cause injury to a limb or other part of a human body. Such an anti
25 pinch function must also reverse the motion such to open the window or door upon detecting a pinch in order to free as quickly as possible the obstacle.

A problem is that comparing the instantaneous current or speed with a threshold is not sufficient to have a reliable detection of an excessive torque. In effect, the motor current I_M may vary for other causes than that of an obstacle blocking the movement of the part moved by the motor.

For a DC motor it is possible to write the following relations:

- $V_M = L_M \cdot dI_M/dt + R_M \cdot I_M + E_M$, where V_M is the supply voltage of the motor, I_M is the current, L_M is the inductance of the motor, R_M is the resistance of the motor and E_M is the back electromotive force;
- 5 – $E_M = k \cdot S_M$, where S_M is the rotation speed of the motor and k is a constant;
- $K_M = k' \cdot I_M$, where K_M is the motor torque and k' is a constant; and
- $K_M - K_R = J_M \cdot d\Omega_M/dt$, where K_R is the resisting torque, Ω_M is the speed of the motor and J_M is the moment of inertia of the rotor.

10 The back electromotive force of the motor is thus directly proportional to the rotation speed thereof while the motor torque is directly proportional to the current. Except where expressly indicated, the word torque in the ensuing description indicates the motor torque against the resisting torque representing the mechanical load (e.g. the weight of the glass window) plus the friction (of the edges of the glass pane sliding in the door guides).

15 Figure 2 is a diagram showing the range of variation and the general characteristic of the current I_M flowing in the motor when closing a car window by lifting it up to its end of run. For sake of simplicity, oscillations of the current due to noise (switchings of the motor brushes on the collector) are neglected.

20 The curve 21 (solid line) illustrates a mean functioning, that is the closing of the glass pane under mean hygrometric and temperature conditions.

The user pushes a command button producing a close-window command that is sent to the controller 10. The switches SW1 and SW4 or SW2 and SW3, depending on the transmission, are turned on and the motor is powered. When the motor is switched on (instant t_0) the current I_M flowing in its windings increases
25 though the speed is still null. The torque that is proportional to the current I_M increases. At a time t_1 , the current I_M drops because the motor is starting to rotate.

The start of rotation reduces the torque and thus the absorbed current, until the time t_2 when the current raises again. The instant t_2 coincides with the moment at which the glass pane (initially wholly retracted inside the door) is braked by the horizontal gasket. Thereafter the torque and the current I_M continue to increase but
5 at slower rate during the lifting of the glass pane.

Upon approaching the end of the lift run current and torque drop because of the higher speed acquired by the glass pane and upon abutting against the upper glass edge receiving channel, at t_4 , the speed becomes zero and the torque increases abruptly.

- 10 End of run detection is generally carried out by means of a position sensor that switch off the power to the motor with consequent drop to zero of the current.

The curve 22 traced with short dashes represents the current (and thus the motor torque) in case of a wet glass subjected to a reduced braking action by the gasket. The curve 23 traced with long dashes represents the case of an iced glass. In this
15 case, the torque necessary to lift the glass is definitely greater.

Should a relatively yielding obstacle (for example, a wrist) interfere with the lift run of the glass pane, the run will be braked by the obstacle before being definitely stopped. The motor will decelerate more or less abruptly, which implies a drop of its back electromotive force and, as a consequence, a rise of the current
20 for increasing the torque.

In the absence of safeguard, an automatic lift of the glass could be dangerous. Should a rigid (unyielding) obstacle be encountered similar consequences are produced characterized by an instantaneous drop to zero of the rotation speed and thus a more abrupt increase of the torque.

- 25 A difficulty of reliably detecting a blocked condition or an abrupt deceleration is that for safety reasons the limit of tolerable compression of a limb or finger may correspond to or be even weaker than the required lifting force (accounting for the case of an iced glass window).

Another difficulty is that the required lifting force may increase in time because of the aging of gaskets and linings and of progressive deformations of parts of the mechanism and of the window structure.

Another difficulty is that abrupt variations of the motor torque stochastically occur when lifting the window pane, for example when the car is travelling a road with an irregular paving. Such in an occurrence, illustrated by the dot and dashed peak 24 of the curve 21 of Figure 2, the resisting torque increases abruptly when a wheel of the car rolls out of a pot hole. The torque and thus the current fall abruptly. When the wheel gets out of the hole, the inverse phenomenon is produced, that is the motor torque increases abruptly, and thus the current flowing in it.

For these reasons that render current monitoring approaches based on the fixing of thresholds hardly discriminating, other techniques have been proposed and are currently used.

Typically, mechanical or electromechanical devices are used as anti-pinch sensor. Deformation of an elastic element between a mechanical detector and the moving glass, when a body is being pinched, is a known approach. This technique requires the use of an elastic conducting element of complex and costly installation.

Pinch detection may be performed by a switch fitted in a weather strip of the car window. The switch that is normally off switches on when the weather strip is subjected to a certain force.

This solution is rather simple but the particular weather strip assembly implies a certain mounting complexity and maintenance may become necessary to maintain effectiveness. Moreover, in some cases this approach does not meet safety specifications. For instance, if the shape of the window determines a very slanted weather strip, a pinching force may not be applied in a direction sufficiently orthogonal to the strip, as shown in Figure 3. Therefore, the pressure necessary to activate the switch may not be reached or may exceed the specified maximum value.

Alternative solutions are generally based on monitoring the motor speed by the use of speed sensors (Hall effect sensors, encoders, and alike). When a pinch condition occurs, the motor is blocked and its speed becomes zero. Therefore, a pinch condition causes an abrupt speed variation, that may be detected by speed sensors.

Yet another known solution consists in processing a number of operating parameter measurements such as temperature, supply voltage, motor speed and position of the motorized part for comparing the actual displacement of the moved part in respect to pre-established models. This approach requires a powerful calculator and a large number of sensors for measuring the parameters necessary for the calculations, besides the definition of particularly complex models in consideration of aging effects.

OBJECT AND SUMMARY OF THE INVENTION

The present invention provides in general terms a novel and particularly effective technique for detecting an increase of the torque of a DC motor without the drawbacks and limitations of the known techniques.

More in particular the technique of this invention offers an excellent solution to provide for a reliable and simple anti-pinch systems.

The technique of this invention overcomes the problems due to spurious abrupt variations of the motor torque that may be caused by other events rather than by an accidental pinching.

The invention provides a solution easy to realize that may be embodied in a relatively simple integrated circuit, without requiring specific external sensors.

More in general, the invention provides a method of detection of an increase of the motor torque particularly suited for detecting an accidentally block of the motor.

The method of this invention permits to recognize a blocking condition caused by a resisting force that may be weaker than the force necessary for activating the motor during other functioning conditions.

5 The invention permits detection of a blocked condition (increase of the torque) even when the load of the motor is greater than the limit blocking force and even if the resisting force varies during the motion of the part driven by the motor even in the long term as it is often the case with the aging of parts.

10 More precisely, object of the present invention is a method for detecting variations of the torque of a DC motor, characterized in that it comprises the operations of

- generating a first signal representing the current flowing in the motor;
- multiplying the first signal with a pre-established function producing a product signal;
- 15 – generating a comparison signal to correspond to the slope of the product signal;
- signaling a torque variation if the comparison signal surpasses a certain threshold.

Preferably, the comparison signal is the difference between the product signal and the moving average thereof over a certain time interval ($t-\Delta t_1$; t).

20 Another object of the present invention is a control circuit for detecting a torque variation of an electric DC motor, comprising

- sensing means of the current flowing in the motor, generating a first signal;
- first circuit means for generating a product signal of the first signal by a pre-established function;
- 25 – second circuit means for generating a comparison signal to correspond to the slope of the product signal;
- a comparator of the comparison signal with a certain threshold, signaling a torque variation when the comparison signal surpasses the threshold.

Preferably, the second circuit means comprise a low-pass filter of the product signal and an adder that produces the comparison signal as the difference between the product signal and the filtered replica thereof.

The invention is more precisely defined in the annexed claims.

5 BRIEF DESCRIPTION OF THE DRAWINGS

The different aspects and advantages of the present invention will become even more evident through the following detailed description of embodiments thereof and by referring to the attached drawings, wherein:

Figure 1 is a sketch of a motorized car window;

10 **Figure 2** are time diagrams of the current through the motor;

Figure 3 is a sketch of the motorized glass pane of the window of a car door and the diagram of the force exerted on an obstacle trapped between the closing glass and a window post;

15 **Figure 4** are diagrams illustrating the working principle according to a preferred embodiment of the method of this invention;

Figure 5 depicts an embodiment of the control circuit of this invention;

Figure 6 is a diagram illustrating how the product signal and the comparison signal change when a pinch occurs;

Figure 7 is a diagram of the main signals of the control circuit of Figure 5;

20 **Figures 8a and 8b** illustrate the functioning of a control circuit of this invention in a normal and in a blocked condition of a motorized car window.

DESCRIPTION OF SEVERAL EMBODIMENTS OF THE INVENTION

For sake of clarity, only the steps of the method and the components of the detection circuit of this invention that are necessary to fully understand the invention are depicted and described hereinbelow. In particular, the end-run
25 detectors of a motorized window and the mechanical transmission organs that are driven by the motor are not represented.

Substantially the method of the invention contemplates generating a signal

representing the current flowing in the motor I_M , multiplying this signal by a certain function $W_{M_virtual}(t)$ and generating a comparison signal corresponding to the slope of this product. The comparison signal is compared with a pre-established threshold, signaling a torque variation when the threshold is surpassed.

- 5 The function $W_{M_virtual}(t)$ is preferably a saturated linear ramp function, which is null when the motor is switched on and saturates when the start-up phase of the motor finishes. The advantages of choosing $W_{M_virtual}(t)$ as a saturated linear ramp will be explained later on.

- 10 Such a comparison signal could be generated for instance by deriving a substantially noise-free filtered replica of the product signal or, according to a preferred embodiment of the method of the invention, by subtracting from the product signal an integrated replica thereof. The time constant of integration may be chosen such to let the filtered replica signal track any torque variation that may occur during the normal functioning of the motorized implement but practically
15 results insensible to torque variations due to the presence of an obstacle that blocks the motor. Preferably, the filtered replica is obtained by calculating the moving average of the product signal with an integrator over a time interval $(t - \Delta t_1; t)$ whose duration Δt_1 is greater than the maximum time constant of a torque variation to be ignored and smaller than the minimum time constant of a torque
20 variation to be detected.

The duration Δt_1 is chosen in function of the yielding interval of a part of the human body. It has in fact been found that these yielding times typically last several tens of milliseconds, which makes possible even to discriminate the squeezing of a limb from other events.

- 25 Preferably the signal representing the current in the motor is filtered with a low-pass filter with a time constant of about a millisecond. By doing so the switching noise of brushes and current variations that may be caused by running over pot holes in the carriageway are effectively filtered out and do not influence detection of torque variations due to the blocking of the motor.

According to a preferred embodiment, the function $W_{M_virtual}(t)$ is a saturated linear ramp voltage. It could be possible to choose a constant function $W_{M_virtual}(t)$, but in this case the system would recognize the inrush current of the motor as due to a pinch. In this case, the detection of torque variations should
5 be disabled during the start-up phase of the motor, thus any pinching occurring during the start-up phase would not be detected.

With reference to Figure 4, let us suppose that the motor be started-up with a saturating ramp voltage $V_M(t)$. If there is not any obstacle that blocks the motor, the current flowing in the motor is represented by the curve $I_{M_nominal}(t)$, which
10 is almost constant, otherwise in case of a blockage it is represented by the curve $I_{M_blocked}(t)$. The product of the current I_M flowing in the motor by the saturated linear ramp voltage $W_{M_virtual}(t)$ is a saturated linear ramp $I_{M_nominal}(t)*W_{M_virtual}(t)$ if the motor is not blocked, otherwise it is a saturated parabolic ramp $I_{M_blocked}(t)*W_{M_virtual}(t)$ if an obstacle stops the
15 motor during its start-up phase.

A comparison signal corresponding to the slope of the product signal is a linear ramp signal if the motor is blocked during the start-up phase, otherwise it is equal to a certain constant value. It should be noted that the slope of the product signal when the motor is not blocked is relatively small, because the current in the motor
20 is almost constant. On the contrary, when the motor is blocked the slope of the product signal rises rapidly to large values. This is exploited for discriminating a normal start-up condition from a blocked start-up condition by comparing the comparison signal with a certain voltage threshold.

As it will be evident to the skilled person, the inrush of current at the start-up does
25 not produce any false blockage detection because the function $W_{M_virtual}(t)$ is null when the motor is switched on, and thus it effectively masks the initial abrupt variation of the current I_M .

When the start-up phase finishes, the saturating ramp voltage $W_{M_virtual}(t)$ becomes a constant (e.g. equal to 1) and thus the product signal corresponds to the

current in the motor I_M . Therefore, after the start-up phase the method of the invention substantially contemplates detecting torque variations from variations of the current in the motor.

It is worth noticing that using the method of the invention it is possible to detect a
5 blocked condition even when glass pane is blocked at the turn on of the motor. This cannot be done with known methods that contemplate the use of Hall sensors because these methods are based on the detection of variations of the motor speed.

A control circuit of the invention for detecting the abrupt speed variation of the motor due to a blocked condition by monitoring the current circulating in the
10 motor, is depicted in Figure 5.

A current sensor, not depicted in figure and that may be of any type as commonly employed for this purpose, generates a signal representative of the current circulating in the motor. An optional Low-Pass filter generates a noise-free replica
1 of the signal representative of the current in the motor, a multiplier generates the
15 product signal 2 and an integrator produces a moving average 3 of the product signal. The integrator filters the variations of the filtered signal the characteristics of which make them attributable to an obstacle, and generates the signal 3. Finally, an adder generates the comparison signal 4 as the difference between the product signal 2 and the moving average thereof 3. The logic signal 5 produced by
20 the comparator is active when the comparison signal 4 exceeds the threshold, signaling that a torque variation has been detected.

The comparator COMP compares the signal 4 with a pre-established threshold PINCH_THRESHOLD that when is exceeded generates a comparison signal that
signals that an obstacle is blocking the run of the motor. Variations of current due
25 to strains of the glass pane guides or to particularly low temperature, humidity and dirt typically cause a relatively slow variation of the motor current that is very well discriminated from fast variations due to the presence of a block obstacle.

Figure 6 depicts in a schematic manner the evolution of the product signal and of the comparison signal when a pinch occurs.

Before the pinch, the product signal is a linear ramp and the comparison signal assumes relatively small values. When a pinch occurs, the current, and thus the product signal, increase rapidly according to a typical parabolic curve, while the comparison signal increases following a linear ramp.

- 5 Diagrams of the main signals of the circuit of Figure 5 during a normal run of the motor, are depicted in Figure 7. The initial current peak due to clearances in the transmission organs does not produce sensible variations of the comparison signal.

- 10 After the start-up of the motor (from t_0 to t_2 in Figure 2) and neglecting spurious disturbances and switching noise, the product signal is proportional to the current I_M flowing in the motor and the mean value thereof do not change considerably for different functioning condition (wet, dry or iced glass). Indeed, different operating conditions cause similar variations of the mean value of the respective curve. Moreover, current (torque) variations during normal functioning are
15 significantly slower than a variation caused by the accidental blocking of the motor.

- More generally, for the same travel between two positions, slow variations of the resisting torque (when an additional constant force is applied) for example under certain conditions of humidity, temperature, and the like, modify negligibly the
20 motor torque in respect to the mean value of these rather slow variations of the resisting torque. Therefore, from an assessed maximum variation during normal functioning, it is possible to determine a proper duration Δt_1 of integration for calculating the moving average, for example, by considering the maximum variation as the acceptable limit.

- 25 Figure 8a illustrates the waveform of different signals of a motorized window in absence of accidental blocking of the motor.

Figure 8b illustrates the same waveforms in the case of an accidental blocking of the motor while lifting the window closed.

In Figures 8a and 8b, the instantaneous value of the current in the motor I_M is represented by the curve traced with short dashes. The curve of I_C (which is a noise filtered replica of the current I_M) is traced with a solid line. The waveform of the moving average I_S of the current in the motor is traced with long dashes.

- 5 The curve I_C of Figure 8a is similar to the already described curve 21 of Figure 2. The curve I_S raises slower than I_C and crosses it at an instant t_{11} successive to the inversion of the slope of the signal I_C after the start of the rotation of the motor.

After the instant t_{11} , the curves I_C and I_S coincide at the instant t_{12} during normal operating conditions of the motor and remain identical as long as the window is
10 eventually shut (peak at the instant t_{14}).

The detection of torque variation is disabled upon reaching the end of the run when the close shut condition is detected by commonly used end run detectors (at the instant t_{14}).

- If the glass window is blocked while being lifted (instant t_{13} of Figure 8b), the
15 curve I_C increases faster than the curve of the moving average I_S .

When the difference between the two curves reaches the pre-established threshold value `PINCH_THRESHOLD`, a torque variation is detected.

- An instantaneous drop to zero of the current circulating in the motor is depicted in Figure 8b. This drop to zero of the current is due to an inversion of the direction
20 of the current (not depicted) following a command for pulling down the glass pane. In case of detection of a pinching it is not sufficient to stop the motor but it is necessary to reverse the motor and to pull down immediately the glass pane for freeing the trapped part of the body.

- A feature of the method of the present invention is that the pinching value, which
25 is fixed (`PINCH_THRESHOLD`), is independent from the level of current in the motor. Therefore, the functioning of an anti-pinch system or more generally of a circuit for detecting a torque variation according to this invention, is not affected by the current value of the torque. This means that, independently from the lifting

speed of the glass pane, it is possible to stop any pinching in a very short time. Theoretically, it would be possible to fix a null pinch threshold, so that even the smallest difference would be detected. In practice, the threshold is fixed for a pinching force as weak as possible in consideration of tolerances of the
5 constituting elements of stabilization times of the quantities to be compared. In particular the pinch threshold may be chosen such to correspond to a tolerable pinching force.

Another feature of the present invention is that even abrupt variations of the torque are ignored as long as they do not last. This phenomenon is represented in
10 Figure 8b by the peak 44 of the signal I_M , representing the abrupt current variation caused by the passage of the car on a pot hole while lifting the glass pane. Because of the shortness of the phenomenon, the signal I_S does not vary. Because of the chosen time constant the peak 44 may cause a small variation of I_C as depicted in Figure 8b. This variation besides having a transient character has also
15 a rather small amplitude and thus the discriminating threshold $PINCH_THRESHOLD$ is not reached and thus there is no detection of a pinching.


Yet another feature of the method of the present invention is that a pinching condition may be detected even if the blocked condition is not followed by a yielding.

20 According to the described embodiment of a motorized window, this represents the case in which the blockage of the glass pane is caused by a trapped finger. Even in such an occurrence it will be necessary to free the trapped finger by reversing the motor for pulling down the glass pane. Though the variation of the instantaneous signal I_M is not followed immediately by a variation of the signal I_C
25 (the peak is not detected, because it is filtered by the integrator 32), the blocked condition persists and therefore the signal I_C eventually increases, thus causing the detection of a blocked condition because I_C increases before the signal I_S .

According to this invention, it is not necessary to use sensors of operating parameters of the motor or other external transducers. The current sensing that is

normally performed for controlling the motor is perfectly sufficient also for the aims of torque variation detection of this invention.

- The present invention may be practiced in forms even different from those described for illustrating purposes, as will appear to the skilled person. In particular, selection of the duration Δt_1 and of the time constant T_2 of the noise filter may be easily done by the skilled person on the basis of the indications given in this description, to suit the particular application. In case of a motorized car window, the duration Δt_1 may be comprised between 10 and 200 milliseconds and the time constant T_2 may be comprised between 0.5 and 10 milliseconds.
- 10 Though the invention has been illustrated in relation to an important sample application of a motorized car window, it is applicable to any other kind of implement motorized with a DC motor whenever it is desirable to detect a blocked condition, or a more or less abrupt increase of the motor torque. For example, the invention may be applied to automated doors, gates, as well as to
- 15 motorized conveyors and the like.



CLAIMS

1. A method for detecting variations of the torque of a DC motor, characterized in that it comprises the operations of
generating a first signal (I_M) representing the current flowing in the motor;
5 multiplying said first signal (I_M) with a pre-established function producing a product signal;
generating a comparison signal to correspond to the slope of the product signal;
signaling a torque variation if said comparison signal surpasses a certain
10 threshold.
2. The method of claim 1, wherein said comparison signal is the difference between said product signal and the moving average thereof over a certain time interval ($t-\Delta t_1$; t).
3. The method of claim 2, wherein the duration (Δt_1) of said time interval
15 ($t-\Delta t_1$; t) is greater than the maximum time constant of a torque to be ignored and smaller than the minimum time constant of a torque to be detected.
4. The method of claim 1, wherein said pre-established function is a saturated linear ramp function ($W_{M_virtual}$), which is null when the motor is switched on and saturates when the start-up phase of the motor terminates.
- 20 5. The method of claim 3, wherein said duration (Δt_1) ranges between $10 \div 200$ milliseconds.
6. The method of claim 1, further comprising the operation of preliminarily filtering from noise said signal representing the current flowing in the motor before multiplying it for said pre-established function.
- 25 7. The method of claim 6, characterized in that said filtered signal is generated by a low-pass filter whose time constant (T_2) ranges between $0.5 \div 10$ milliseconds.


8. The method of claim 1, wherein said motor is accelerated during the start-up phase by supplying it with a linear saturating ramp voltage.
9. A method for detecting a blocked condition of an electric DC motor, characterized in that it comprises the steps of
- 5 detecting an increase of the motor torque with the method as defined in any of claims from 1 to 8;
signaling a blocked condition when an increase of the motor torque is detected.
10. A control circuit for detecting a torque variation of an electric DC
10 motor, comprising
sensing means of the current flowing in the motor, generating a first signal (I_M);
first circuit means for generating a product signal of said first signal (I_M) by a pre-established function;
15 second circuit means for generating a comparison signal to correspond to the slope of the product signal;
a comparator of said comparison signal with a certain threshold, signaling a torque variation when said comparison signal surpasses said threshold.
11. The control circuit of claim 10, wherein said first circuit means
20 comprise a low-pass filter that outputs a noise filtered replica of said first signal (I_M) towards said first circuit means.
12. The control circuit of claim 11, wherein said low-pass filter generates said filtered replica signal to correspond to a moving average of said first signal (I_M) and has a time constant (T_2) that ranges between $0.5 \div 10$ milliseconds.
- 25 13. The control circuit of claim 10, wherein said second circuit means comprise a low-pass filter of said product signal, and an adder that generates said comparison signal as the difference between said product signal and the filtered replica thereof.

14. The control circuit of claim 13, wherein said low-pass filter generates said filtered replica of said product signal as the moving average thereof over a certain time interval ($t-\Delta t1$; t) whose duration ($\Delta t1$) is greater than the maximum time constant of a torque to be ignored and smaller than the minimum time
5 constant of a torque to be detected.

15. The control circuit of claim 14, wherein said duration ($\Delta t1$) ranges between $10 \div 200$ milliseconds.

16. The control circuit of claim 13, wherein said first circuit means
comprise

- 10 a waveform generator of a saturated linear ramp signal ($W_{M_virtual}$) which
 is null when the motor is switched on and saturates when the start-up
 phase of the motor finishes;
 a multiplier input with said linear saturating ramp signal ($W_{M_virtual}$) and
 said first signal (I_M), generating a product signal.




**“METHOD AND RELATIVE CIRCUIT FOR DETECTING A TORQUE
VARIATION OF AN ELECTRIC DC MOTOR”**

A B S T R A C T

A method for detecting variations of the torque of a DC motor particularly suited
5 for detecting an accidentally block of the motor, comprises the operations of
generating a first signal representing the current flowing in the motor, multiplying
the first signal with a pre-established function producing a product signal,
generating a comparison signal to correspond to the slope of the product signal
and signaling a torque variation if the comparison signal surpasses a certain
10 threshold.

The method is implemented by a control circuit for detecting a torque variation of
an electric DC motor, comprising sensing means of the current flowing in the
motor, generating a first signal, first circuit means for generating a product signal
of the first signal by a pre-established function, second circuit means for
15 generating a comparison signal to correspond to the slope of the product signal, a
comparator of the comparison signal with a certain threshold, signaling a torque
variation when the comparison signal surpasses the threshold.






FIG. 1





FIG. 2

**FIG. 3**





FIG. 4






FIG. 6






FIG. 7

**FIG. 8A****FIG. 8B**